



STEEL BLASTERS

HUSQVARNA BLASTRAC EBE 900V

Art.no: 970 69 31 01

The Blastrac EBE 900V is a vertical steel blaster ideal for large vertical steel blast cleaning jobs and applications. It is perfect for preparing surfaces before the application of new coatings. It is also ideal for removing coatings and paint from steel surfaces. It is remote controlled for operator comfort and productivity. With its increased production width and greater productivity, Blastrac EBE 900V is ideal for medium and large sized jobs. It is equipped as standard with a certified endless winch system with two 25 meter long winch cables (cable length can be modified) and an integrated closed circuit cooling system inside the electrical box. The Blastrac EBE 900V steel blast cleaning machine is ideally suited for oil/storage/water tank shells, ship hulls and wind mill pipes. Integrated cooling of the electrical system allows for uninterrupted work in high ambient temperatures regions.

FEATURES



Work virtually dust free

The steel blasting machine has to be connected to a Blastrac industrial dust collector to create a closed circuit. This means that you are able to work virtually dust free, creating a better working environment.

Increased productivity with remote control

All the movements of both the rigging system and the vertical blast cleaning machine are controlled from a mobile control station located on the ground floor.

Reach far with endless winch system

The steel blaster is equipped as standard with a certified endless winch system and winch cables. It is possible to blast going both up and down, increasing the productivity of the machine.

Adaptable rigging systems for smooth operation

Blastrac rigging systems have been developed to drive by themselves and to adapt to cone roof tank, dome roof tank, floating roof tank (internal parts) and floating roof tank (external parts).

TECHNICAL DATA HUSQVARNA BLASTRAC EBE 900V

Art.no: 970 69 31 01

HUSQVARNA BLASTRAC EBE 900V

MOTOR

Output power	50 kW
Voltage	400 V
Frequency	60 Hz
Rated current	125 A
Phases	3 ph
Power Source	Corded

PRODUCT DATA

Working width	89 cm
Dust hose connection	150 mm
Steel shot consumption	1,000 g/m ²
Productivity	120 m ² /h

TRANSMISSION

Type of operation	Remote-controlled
-------------------	-------------------

DIMENSIONS

Product size length	1,463 mm
Product size width	1,145 mm
Product size height	1,480 mm
Weight (complete product w/o side packed articles)	880 kg



View all product details on:

<https://www.husqvarnaconstruction.com/int/steel-blasters/blastrac-ebe900v/>